








Available top cap options

The OTT ecoLog 500/800 is installed by simply hanging it into observation wells of 2" diameter and greater. For this purpose, various top caps, adapters and suspension brackets are available as accessories. Tops offered by OTT ensure reliable GSM signal strength.

		OTT ecoCap	OTT top cap with stub antenna	OTT vented plastic top cap		
						
		<ul style="list-style-type: none"> - Robust aluminium housing, weather proof antenna protection cover, ABS plastic with UV resistant coating - Secures on well without threads - Specifically designed for ecoLog 500/800 - Tamper proof and lockable – uses Pentagon wrench - Versions 3" and 4" are built for use with contact gauges 	<ul style="list-style-type: none"> - Heavy duty metal construction with robust antenna cover - Threads on to well pipes w. BPT threads - Comes with antenna cable to attach ecoLog antenna to antenna cover - Tamper proof and lockable – uses Pentagon wrench - Available as retrofit kit for use with existing installations without antenna cover 	<ul style="list-style-type: none"> - UV protected heavy duty nylon construction - Features "gripNLock": concentric rings inside the cap secure the cap on the well - Install using a hammer or mallet - Embossed monitoring well label - Lockable with padlock 		
		top caps	top caps	adapter plates	top caps	adapter plates
Well diameter	2"	55.446.015.9.2 (Version 2", 3", 4")	55.446.030.9.2		24.220.099.3.2	
	3"	55.446.017.9.2 55.446.015.9.2 (Version 2", 3", 4")	55.446.031.9.2	55.446.022.9.2		
	4"	55.446.016.9.2 55.446.015.9.2 (Version 2", 3", 4")	55.446.032.9.2	55.446.023.9.2	24.220.100.3.2	55.446.424.3.1
	5"	use 4" top cap 55.446.016.9.2 with pipe extender 55.530.479.3.1	55.446.033.9.2	55.446.025.9.2		
	6"	use 4" top cap 55.446.016.9.2 with pipe extender 55.530.480.3.1	55.446.034.9.2	55.446.026.9.2		
Accessories:	Pentagon wrench: 20.250.095.4.1	Pentagon wrench: 20.250.095.4.1				

Flexible installation options

		Universal suspension bracket - For use in well > 3"		55.446.021.9.2
		External antenna - Provides option to bring antenna outside metal well pipe or housing - SMA Antenna connector - Field exchangeable - Replaces standard ecoLog stub antenna	0.5 m cable 1.0 m cable 1.5 m cable 5.0 m cable	97.980.131.9.5 97.980.132.9.5 97.980.133.9.5 97.980.134.9.5
		Retrofit kit for existing top caps: - E.g. OTT top cap - Uses ecoLog stub antenna - Threads in existing thread or fixed with screw nut		55.446.035.9.2