



## All-weather, high accuracy rain gauge for continuous data collection

- Parameters measured**  
 Cumulative precipitation, precipitation intensity, bucket content in real time and non real time
- Measurement technology**  
 Weighing principle
- Product Highlights**  
 All-weather precipitation gauge without moving parts according to WMO guide line No. 8
- Interface**  
 SDI-12 / RS-485, pulse

The OTT Pluvio<sup>2</sup> is an all-weather precipitation gauge that uses superior weight-based technology to measure the amount and intensity of rain, snow, and hail. Developed in conjunction with industry-leading meteorological services, the OTT Pluvio<sup>2</sup> employs a high-precision load cell and algorithms that compensate for wind, temperature, and evaporation, ensuring the highest accuracy precipitation measurements over time.

Types of precipitation	liquid, solid, and mixed
Collecting area	200 cm <sup>2</sup> and 400 cm <sup>2</sup>
Collection volume	1500 mm/m <sup>2</sup> and 750 mm/m <sup>2</sup>

**Measuring range 200 cm<sup>2</sup>**

Intensity RT / measuring interval 1 minute	12.00 ... 1800.00 mm/h, 0.20 ... 30 mm/min
Amount RT/NRT, amount NRT, amount total NRT	0.10 ... 500.00 mm
Bucket content, RT and NRT	20.00 ... 1600.00 mm

Measuring range 400 cm <sup>2</sup>	
Intensity RT / measuring interval 1 minute	6.00 ... 1800.00 mm/h, 0.10 ... 30 mm/min
Amount RT/NRT, amount NRT, amount total NRT	0.10 ... 500.00 mm
Bucket content, RT and NRT	20.00 ... 850.00 mm

Accuracy (at - 25 ... +45 °C)	
Amount, absolute (60 minutes collection time)	± 0.05 mm
Intensity	± 0.1 mm/min or ± 6 mm/h

Resolution	
Impulse output	0.1 mm
SDI-12 and RS-485	0.01 mm/min, 0.01 mm/min or mm/h

Times	
Intensity output interval	1 minute
Output delay	RT 20 seconds; NRT 5 minutes
Query interval	6 seconds ... 60 minutes

Interfaces	
USB	configuration/service mode and firmware update
Serial interfaces	SDI-12 or RS 485
Digital outputs	impulse 0.1 mm (configurable) and status (0 ... 120 impulses/min; configurable 5 or 2Hz )
Measurement output	intensity RT; amount RT/NRT, amount NRT, amount total NRT, bucket content RT and NRT; temperature of load cell, status Pluvio <sup>2</sup> , status heating (if present)

Electrical and mechanical data	
Sensor element	sealed load cell
Power supply	10 ... 28 VDC
Power/current consumption	typ. 12 mA at 12 V
Ring heating, optional	Pluvio <sup>2</sup> 200: 24 VDC / 50 Watt Pluvio <sup>2</sup> 400: 24 VDC / 100 Watt

Dimensions (Ø x h)	
OTT Pluvio <sup>2</sup> 200 / 400	450 mm x 740 mm / 450 mm x 660 mm
Pedestal	(Ø) 110-120 mm ( 4 ')

## 2-3

We reserve the right to make technical changes and improvements without notice. V-03/07/2024  
OTT Hydromet GmbH, Germany



**Weight** (bucket empty) 15 kg

**Material for base plate / bucket /** stainless steel, aluminium / polyethylene / ASA, UV- resistant  
**pipe housing**

## Environmental conditions

Temperature, in operation	-40 ... +60 °C
Temperature, storage	-50 ... +70 °C
Relative humidity	0 ... 100% (non-condensed)

## Protection

Housing	IP54, resistant to salt fog
Load cell / electronics	IP67 / IP64

**EMC** EN 61000-4-2/4/5/6, Level 5 (4 kV) EM/EMI EN 61000-4-3, CE conformity

RT = real- time; NRT = non real-  
time ; units can be configured in  
mm or in (inch) and °C or °F